



**Galaxy Fuji lift you up**

## **GALAXY FUJI ELEVATOR CO., LTD**

Address: 1st Floor, No. 10, Lane 255, Xiaotang Road, Fengxian District, Shanghai, China

KATHERINE

MP: +86 19888125655

Email: [katherine.galaxyfuji@gmail.com](mailto:katherine.galaxyfuji@gmail.com)

---

CHARLEY

MP: +86 13671543901

Email: [charley.galaxyfuji@gmail.com](mailto:charley.galaxyfuji@gmail.com)

Facebook: [Galaxy Fuji Elevator](#)

---



**GALAXY FUJI ELEVATOR CO., LTD**





# CONTENTS

---

<b>Passenger Elevator</b> .....	03
<b>Villa Elevator</b> .....	15
<b>Observation Elevator</b> .....	21
<b>Freight Elevator</b> .....	25
<b>Bed Elevator</b> .....	27
<b>Decoration Spare Parts</b> .....	29
<b>Moving Walk</b> .....	35
<b>Escalator</b> .....	37
<b>Shopping Cart Elevator</b> .....	41
<b>Automobile Elevator</b> .....	43
<b>Dumbwaiter Elevator</b> .....	44
<b>Vertical Platform Lift</b> .....	65
<b>Inclined Elevator</b> .....	69
<b>Hydraulic Guide Rail Cargo Elevator</b> .....	71
<b>Car Parking Lift</b> .....	73
<b>Photovoltaic Power Generation System</b> .....	75
<b>Elevator &amp; Escalator Modernization</b> .....	77



We have been growing to become the market and innovation leader for elevator business. Our company, which has been acting with the experience and knowledge gained in the sector for many years, continues to maintain its friendly and quality service understanding.

Our company is based on marketing experience. It is our challenge to enable clients to turn opportunities into real value-added business. We offer machines and services with high value retention. By doing so, we ensure process reliability and efficiency for customers all over the world. We perform fully detailed market analysis and define jointly with you the required measurements and actions.

With the knowledge and experience that years have contributed to us, we ensure that our products meet with the end consumer by determining the correct market analysis and hot sales channels on site. That's what define us and what motivates us.



# High-end Business

## Passenger Elevator Standard Car Decoration

The unique hairline stainless steel car made by GALAXY FUJI mixes with a distinctive ceiling creates exciting visual effects and bright contemporary look.



### GF-JX18<sup>^^</sup>

- Ceiling:** Simple paint roof with soft LED lighting
- Car wall:** Hairline stainless steel
- Operating panel:** Integrated operating panel
- Handrail:** Stainless steel flat handrail
- Floor:** PVC

### GF-JX12<sup>^^</sup>

- Ceiling:** Diamond silver painted steel with acrylic photic board.
- Car wall:** Hairline stainless steel
- Operating panel:** Integrated operating panel
- Handrail:** Stainless steel flat handrail
- Floor:** PVC



Landing door and jamb: Hairline stainless steel is adopted for the first floor and plastic jet steel plate is adopted for other floors.




## GF-JX03»»

**Ceiling:** Mirror stainless steel frame, arch white light-emitting panel, down lamp  
**Car wall:** Hairline, mirror, etched stainless steel  
**Handrail:** Triple stainless steel tube  
**Floor:** PVC(Optional marble)



## GF-JX07»»

**Ceiling:** Hairline stainless steel, central acrylic, two-side transparent organic light poles  
**Car wall:** Mirror stainless steel, hairline stainless steel  
**Car door:** Stainless steel flat handrail  
**Floor:** PVC(Optional marble)



## ««GF-JX04

**Ceiling:** Painted steel plate frame, acrylic light-emitting panel  
**Car wall:** Etched mirror stainless steel, hairline stainless steel  
**Handrail:** None  
**Floor:** PVC(Optional marble)



## ««GF-JX08

**Ceiling:** Champagne gold mirror stainless steel, central soft lighting design of arch white organic light-emitting panel, LED  
**Car wall:** Hairline stainless steel  
**Handrail:** Stainless steel single tube  
**Floor:** PVC(Optional marble)

## GF-JX09»»

**Ceiling:** Mirror stainless steel, central acrylic, two-side transparent organic light poles  
**Car wall:** Mirror stainless steel, hairline stainless steel  
**Car door:** Stainless steel flat handrail  
**Floor:** PVC(Optional marble)



## GF-JX11 »»

**Ceiling:** Hairline stainless steel, central acrylic, two-side transparent organic light poles  
**Car wall:** Mirror stainless steel, hairline stainless steel  
**Car door:** Stainless steel flat handrail  
**Floor:** PVC(Optional marble)



## ««GF-JX10

**Ceiling:** Mirror stainless steel Acrylic lighting decoration, led lighting  
**Car wall:** Mirror, etched, Hairline  
**Handrail:** Stainless steel flat handrail  
**Floor:** PVC



## ««GF-JX12

**Ceiling:** Hairline stainless steel, central acrylic, two-side transparent organic light poles  
**Car wall:** Mirror stainless steel PVC decorating gem, Mirror stainless steel  
**Handrail:** None  
**Floor:** PVC



# Extravagant Atmosphere



## GF-JX13 »

**Ceiling:** Soft lighting design of broad arch white light emitting panel

**Car wall:** Titanium gold, mirror, etched, hairline, irregular grain

**Handrail:** Round wood and titanium gold combined handrail

**Floor:** PVC



## « GF-JX14

**Ceiling:** Painted modelling stainless steel, mirror stainless steel, down lamp

**Car wall:** Titanium gold mirror stainless steel, titanium gold etched mirror

**Handrail:** None

**Floor:** PVC(Optional marble)



## GF-JX15 >>

**Ceiling:** Stainless steel, acrylic lighting decoration down lamp  
**Car wall:** Veneer panel, etched mirror  
**Handrail:** Solid wood and titanium round handrails  
**Floor:** PVC



## GF-JX17 >>

**Ceiling:** Titanium gold mirror stainless steel, acrylic lighting decoration, led lighting  
**Car wall:** Titanium gold, mirror, etched, Hairline, irregular grain  
**Handrail:** T- plated stainless steel flat handrail  
**Floor:** pvc



## << GF-JX16

**Ceiling:** Mirror stainless steel, acrylic lighting decoration down lamp  
**Car wall:** Veneer panel, etched mirror  
**Handrail:** Solid wood and stainless steel round handrails  
**Floor:** PVC





## << GF-JX18

**Ceiling:** Titanium gold mirror stainless steel, acrylic lighting decoration, LED lighting  
**Car wall:** Titanium gold, mirror, etched, hairline  
**Handrail:** T- plated stainless steel triple tube  
**Floor:** PVC



## GF-JX19 >>

**Ceiling:** Stainless steel, acrylic lighting decoration down lamp  
**Car wall:** Veneer panel, etched mirror  
**Handrail:** Solid wood and titanium round handrails  
**Floor:** PVC



## << GF-JX20

**Ceiling:** Painted Steel, Acrylic lighting decoration  
**Car wall:** Wood Decoration, mirror stainless steel  
**Handrail:** Solid wood and titanium round handrails  
**Floor:** PVC

## GF-JX21 >>

**Ceiling:** Bronze mirror stainless steel frame, hollow design, organic lighting decoration, LED light  
**Car wall:** Bronze mirror etching, bronze hairline stainless steel  
**Handrail:** None  
**Floor:** PVC (Optional marble)



## << GF-JX22

**Ceiling:** Bronze mirror stainless steel, acrylic light-emitting  
**Car wall:** Mirror stainless steel, bronze mirror etched stainless steel  
**Handrail:** Combination of solid wood and bronze stainless steel  
**Floor:** PVC (Optional marble)

# Villa Elevator

GALAXY FUJI villa elevator adheres to the design idea of environmental protection and energy-saving and merges with the latest elevator technology nowadays in order to ensure safety and reliability of our products. The elegantly designed car, fine and exquisite craft and techniques show the outstanding performance and charm of GALAXY FUJI villa elevator. "The journey scene" matches perfectly with the deluxe and fashionable villa. It is so comfortable and convenient in using GALAXY FUJI villa elevator. You will enjoy your noble life as well.



## GF-VL09»»

- Ceiling:** Hairline stainless steel, acrylic lamp
- Back wal:** Mirror stainless steel, etching
- Side wal:** Mirror stainless steel, etching
- Front wall:** Hairline stainless steel
- Car door:** Hairline stainless steel
- Floor:** Aluminum honeycomb marble



## «« GF-VL10

- Ceiling:** Woodiness baking paint (ivory), white transparent marble in the middle
- Back wall:** Woodiness baking paint (ivory), cosmetic mirror
- Side wall:** Woodiness baking paint (ivory)
- Front wall:** Hairline stainless steel
- Car door:** Hairline stainless steel
- Floor:** Aluminum honeycomb marble



## GF-VL11 >>

**Ceiling:** Mirror stainless steel, acrylic printing  
**Back wall:** Etching stainless steel with champagne gold mirror, both sides of the champagne gold mirror stainless steel  
**Side wall:** Wooden finish with seam stitching, mirror stainless steel  
**Front wall:** Mirror stainless steel  
**Car door:** Mirror stainless steel  
**Floor:** Aluminum honeycomb marble mosaic, copper strip




## << GF-VL12

**Ceiling:** Wooden top, LED lamp  
**Back wall:** Wood veneer, mirror stainless steel  
**Side wall:** Wood finishes  
**Front wall:** Mirror stainless steel  
**Car door:** Mirror etching stainless steel  
**Floor:** Aluminum honeycomb marble

## GF-VL13 >>

**Ceiling:** Rose gold mirror stainless steel frame, central acrylic decoration, LED lamp  
**Back wall:** Rose gold etching  
**Side wall:** Rose gold, mirror, etching stainless steel  
**Front wall:** Rose gold hairline stainless steel  
**Car door:** Rose gold hairline stainless steel  
**Floor:** Aluminum honeycomb marble



## << GF-VL14

**Ceiling:** Rose Gold Mirror Frame, Hollow Pattern  
**Back wall:** Rose Gold Mirror Etching, Plus The Decorative Wooden Plate, Mirror Stainless Steel Inlaid  
**Side wall:** Rose Gold Mirror Etching, Plus The Decorative Wooden Plate, Mirror Stainless Steel Inlaid  
**Front wall:** Rose gold hairline stainless steel  
**Car door:** Rose gold hairline stainless steel  
**Floor:** PVC



## Gantry Frame Villa Elevator

### Features of Gantry Frame Structure Products

Such kind of elevator drive host is beside the well-top. Two main rails are in left | right of elevator car. Therefore car gets even encountered force on both sides. It brings about the more smooth elevator operation and more perfect travel. At present, composite steel band traction and wire rope traction style products are available for your free choices.

- Even encountered force to elevator car,
- Smooth operation, comfortable travel;
- Longer service life of elevator parts;
- As far as elevator with wire rope traction is concerned, it has the higher requirements to pit and top-floor height.



## Steel Band Villa Elevator

New type steel band traction home elevator products, its wall decoration for Mosaic on three sides, with the middle decorative detachable, can use different material, interchangeability stronger and can meet the customer diversification and personalized needs.

### The three big advantage

1. Polyurethane (PU) material layer without lubrication.
2. Its life is two or three times higher than that of traditional wire rope.
3. It is more bendable. It increases the contact area with drive wheel. It is more effective and energy-saving.



Composite steel belt





# Observation Elevator

GALAXY FUJI observation elevator applies the advanced WVF frequency, voltage, speed regulation devices, gearless drive mode, shock absorbing technology. It designs the best running curve according to human-body physiological requirements. GALAXY FUJI observation elevator keeps smooth and comfortable travel enjoyment and visual aesthetics during start, acceleration, deceleration, parking process. It increases elevator quality to a new level.

GALAXY FUJI observation elevator has delicate visual aesthetics, perfect & comfortable travel. It provides you with smooth and comfortable travel experience.

Therefore you get pleasant enjoyment in short journey.



## GF-OL01 »»

**Upper and lower guard:** Stainless steel color steel plate, outer cladding of titanium gold stainless steel

**Observation wall:** Safety laminated glass

**Decoration roof:** Safety laminated glass

**Car wall:** Hairline stainless steel wall, vertical column of front wall

**Handrail:** Stainless steel double handrails

**Floor:** PVC



## « GF-OL02

**Upper/lower cover:** Steel plate baked enamel, decoration lamp

**Observation wall:** Safety laminated glass

**Decoration top:** Mirror stainless steel, acrylic top panel, LED lighting

**Car wall:** Hairline stainless steel

**Handrail:** Stainless steel mono-tube

**Floor:** PVC (Optional marble)



## GF-OL03 >>>

**Upper and lower guard:** Baked enamel steel, milky white acrylic decoration  
**Observation wall:** Laminated safety glass  
**Decoration roof:** Mirror stainless steel framework, milky white acrylic decoration, down lamp on the sides  
**Car wall:** Combination of mirror stainless steel and laminated glass  
**Handrail:** Stainless steel round tube handrail  
**Floor:** PVC



## << GF-OL04

**Up and Bottom Canopy:** Yellow titanium gold mirror stainless steel  
**Observation wall:** Detached transparent laminated glass  
**Decoration roof:** Mirror stainless steel framework, acrylic light-emitting panel down lamp on the sides  
**Car wall:** Laminated safety glass.  
**Handrail:** Stainless Steel round tube handrail  
**Floor:** PVC

## GF-OL05 >>>

**Up and Bottom Canopy:** Painted steel, milky white acrylic cover  
**Observation wall:** Laminated safety glass  
**Decoration roof:** Hairline stainless steel, acrylic lighting decoration  
**Car wall:** Hairline stainless steel  
**Handrail:** Stainless Steel tube  
**Floor:** PVC



## << GF-OL06


**Ceiling:** Mirror stainless steel frame with acrylic lighting  
**Cabin:** Glass with stainless steel titanium plated  
**Floor:** PVC



## Freight Elevator Car Decoration

### GF-FL01 >>

**Car wall:** Painted steel  
**Ceiling:** Painted steel  
**Lighting:** Fluorescent lamp  
**Car door:** Painted steel  
**Floor:** Checked steel plate



### << GF-FL02

**Car wall:** Hairline stainless steel  
**Ceiling:** Hairline stainless steel  
**Lighting:** Fluorescent lamp  
**Car door:** Hairline stainless steel  
**Floor:** Checked steel plate

## Control operation panel and hall buttons

Simple and elegant buttons handling facility,  
matching the diversified and personalized cabin to a greater extent.



GF-H01C



GF-H01X

### Floor optional



GF-HDB01  
Checked steel plate

### Crash barrier elevator



Wooden




Black rubber



## Bed Elevator Car Decoration

### GF-BL01 >>

**Car wall:** Hairline stainless steel  
**Ceiling:** Hairline stainless steel ,vaulted light board with acrylic  
**Handrail:** Stainless steel flat handrails  
**Floor:** PVC



## Bed Elevator

Bed elevator often competes with time in vast hospitals, modern medical treatment centers, sanatoriums, medi-care centers etc. where healing the wounded and rescuing the dying are the bounden duties. GALAXY FUJI bed elevator series adhere to the persistently humane thinking, apply fuzzy logic and group supervision technology from expert system, fulfill the intellectual elevator travel and reduce the patients' waiting period to minimum extent.



### << GF-BL02

**Car wall:** Painted steel(Cream-colored)  
**Ceiling:** Painted steel,LED lighting  
**Handrail:** Stainless steel tube  
**Floor:** Checked steel plate



# MAN-MACHINE INTERFACE



## CEILING SERIES




## LANDING DOOR SERIES






## HANDRAIL SERIES



## FLOOR PVC SERIES



## COLOR CARD SERIES



· The pictures are plotted by computer and are likely somewhat different from the actual products.

## Comprehensive Security System

The GALAXY FUJI escalator series adopts a novel, fashionable and creative design, and quietly waits in every corner of the city in an elegant and atmospheric manner.

The strength of the carrying capacity, all of which highlights its advanced technology, reliable carrying and comfortable ride. Industry-leading innovative technology to achieve safe, energy-saving, environmentally friendly green operation, and promote the sustainable development of the city.



### Energy-saving safety device

The integration of a number of international leading technologies and energy-saving safety devices completely eliminates the conventional hidden dangers of ladder chain looseness, step and apron plates, and comb-tooth plate friction, and regular maintenance to ensure safe and smooth operation.



### Microcomputer control technology

Adopting international leading computer control technology, controlled by CPU motherboard computer, It can fully monitor the running status of the escalator, detect and eliminate potential safety hazards in time, and ensure the safety of passengers.



### Real-time online monitoring


Real-time online monitoring of escalator and sidewalk operations,  
Achieve fault warning,  
Prevent the occurrence of major accidents,  
The first time I found the elevator malfunction,  
The first time to solve the fault.



## 21 national standards development and multiple guarantees for technology patents

Standard safety device	
1 Drive chain break protection	8 Electrical circuit protection
2 Step lighting	9 Motor overload protection
3 Emergency stop button	10 Phase loss, misalignment protection
4 Handrail belt break protection device	11 Overspeed protection
5 Comb plate safety protection device	12 Non-operational reversal protection
6 Brake protection	13 Overhaul safety switch
7 Drive chain break protection	14 Start the alarm device


Standard safety device	Optional safety device
15 Cascade collapse protection device	22 Additional brake (H>6m must be equipped)
16 Warning line	23 Lower machine room drainage
17 Handrail speed monitoring	24 Lower machine room water level detection (outdoor ladder)
18 Apron brush	25 Oil water separator (outdoor ladder)
19 Handrail with entrance protection	
20 Cascade chain break protection	
21 Step loss protection	



## Optional function

### Comb-board Lighting

White/blue/red



### Handrail color

Gray/red/orange/blue




### Voice HMI system

Voice prompt ride considerations



### Comb

Aluminum alloy



### Front panel, floor panel


Aluminum alloy



## Perfect layout


### Intermittent layout (one-way traffic)

Suitable for operation between three floors in a smaller mall.




### Parallel continuous arrangement (two-way traffic)

This kind of separation is not very convenient for the customer, but it is very advantageous for the owner of the store, because you can provide them with special services on the way to the escalator.




### Cross-continuous arrangement (two-way traffic)

The cross-continuously arranged escalators installed in multiple floors can serve two running directions. This form is mostly used in shopping malls, and now more and more used in government agencies and public places, it can reduce between small main floors. Running time.



### Continuous layout (one-way traffic)

A continuous configuration of escalators or sidewalks that connect several floors. It requires more space than intermittent.






## Shopping Cart Elevator



### Variety advantages of shopping cart transport equipment

It applies advanced German technology. It is stable in running rail, convenient in maintenance, fine and exquisite in structure, attractive in outline. After shopping cart is moved in shopping cart transport equipment shopping cart jointly moves with escalator along rail. Passenger is separated from shopping cart. It increases security. It reduces consumer's burden. It is especially helpful for the old, the weak, kids, the disabled. It also shows great caring to consumers from shopping centers.

## Shopping cart elevator construction layout diagram





## Automobile Elevator

It creates new height of vertical automobile transport.

Functions of GALAXY FUJI automobile elevator are similar to that of heavy load freight elevator. It fulfills free up / down of automobiles in vertical spaces. In the aspect of design, it fully considers big space, heavy load that are required by automobile loading / unloading. It applies advanced freight elevator technology with reliable performances, flexible parking, convenient use. It is applicable for large size shopping center, logistics center, car 4S shop etc.



## Dumbwaiter Elevator

Slideway with the novel design

Central double section materials special slide way with unique design connects with operation through door slider. It reinforces smooth elevator door opening, reduces door sheet gap. It is convenient for installation and adjustment.



GF-ZE001  
Windows type



GF-ZE002  
Floor type





## Passenger Elevator Function


Standard Function	
Full collective control	Controller will automatically select the nearest elevator responding passenger's call.
Inspection operation	Automatically move to the nearest leveling in a slow speed
Automatic backplane	In normal condition, the elevator will automatically move to the nearest leveling in a slow speed.
Automatic door opening	Elevator open the door automatically.
Automatic door opening time adjustment	Door remaining open for a short time in normal condition.
Door opening button(external)	Door remaining open when the door opening button was pushed on.
Door pre-closing function	To make door close immediately in normal opening condition.
Door opening button (internal)	To make door open or reopen when elevator stops.
Full load bypass	When the elevator is fully loaded, it will travel to destination without responding to calling outside.
Automatic turn off lighting and fan	Lighting and fan will cut off power automatically without any call or indication in 3 minutes.
Automatic return to home landing	In normal condition, the elevator will return to home landing without any more calls or indications.
Door re-closing	The door will try to close again when it is blocked.
Error recording	Main board can record 10 errors at most.
Hoistway self learning	Elevator can learn the data and situation automatically before using.
Attendant service	The lift is closed by continued pressing close buttons.
Bypass operation	Elevator will travel directly to destination without stopping.
Automatic correction of floor position signal	Self correcting the data when the elevator reach final limit switch.
Lift locking	Lock the elevator and turn off the power so that no one can use it.
Protection of door lockup outside door area	No door opening when it is not in leveling position.
Infrared light curtain protection	Door will opening when it is blocked.
Overload protection	Elevator travel with buzz when it is overloaded.
Reversal running protection	When the running direction is different with destination direction, it stops automatically.
Anti skip protection	Traveling a long time without door opening, it will stop automatically.
Anti terminal over running protection	Security risks are prevented by preventing the continued operation of the failure of the terminal switch.
Phase protection	Stop to move when the final limit switch fails to have function.
Phase protection	The elevator will stop with wrong phase or lack phase.
Contact protection	Stop running when safety devices conflict.
Failure analysis of shaft self learn	When the shaft learned by itself that it doesn't finished it correctly.
Motor temperature protection	Protect the motor from being over heat.

Standard Function	
Door opening failure protection	Stop running when error happens to door.
Protection for door lock short circuit	Elevator refuse to move when error suddenly happens to the brake.
Door lock failure for brake switches	Elevator will stop at once when error suddenly happens to door lock.
Over speed protection	In case of elevator running too fast.
Contact protection for brake switches	Protect the elevator when error happens to the brake.
Five-party interphone communication	Communication for machineroom, car top, car cage, pit and inspection station.
Wheeling protection	Safety protection is rescuing.
Alarm bell	When the anomaly occurred, passenger in the cabin can notice the outside with this device.
Emergency lighting	When the power supply is failure, it can provide the lighting of the car.
Two doors operator	Only for opening through door opening type.
Level switch protection	It is a safety protection in case of the trouble in leveling switch.
False call canceling	When the passengers press the false button, it can cancel the call through the two times press.
Automatic reversal call canceling	When the running direction is different with destination direction, it stops automatically.
Floor display directional setup	Directional setup of service floor.
Isolate running	Operation similar to attendant service function.
Segment code or dot matrix floor indicator	The indicator displayed in dot matrix type.
Rolling display of running direction	The running direction display in a rolling way.
Forced door closing	The door nudging device will force the door closing when it open too long.
CAN Communication protection	Prevent the danger in case of trouble.
Arrival gone	Sound to indicate leveling is finished.
Emergency return in case of fire	The elevator will return to home floor in a short time when fire emergency happens.
Main control protection	Stop the running of the elevator in case of trouble.
Main control CPU WDT protection	When test the trouble of CPU, WDT make it reset.
Discretionary and setup of service floor	Using the operator to setup the landing floor discretionary.
Test running	It is used for testing the new elevator.
Clock control	It can record the time of trouble, and decide to stop at any floor.
Direct landing	The efficiency of the elevator can be improved by the distance principle to deceleration.
Load weighing device	With such system, the elevator can self learn the data to improved the start up.
Parallel control	Two elevator through the CAN serial communication bus to coordinate the call.
Protection device for accidental movement of the car	In case of accidental movement that the car leaves the landing floor while the landing door is unlocked as well as the car door keeps open protection device to prevent or stop such movement should be equipped.
Bypass protection	Bypass protection provides safety protection for daily maintenance.

## Freight Elevator Function

Standard Function	
IC card management	Users can control the certain floors with this card.
Voice announcer	Voice announcement for running situation
Automatic rescue device (ARD)	The elevator will automatically run to the nearest door zone when the power supply fails.
Advance door opening	In process of leveling, the distance is right, and the speed is little than the regulated one, the door will open in advance.
Arrival forecasting light	Flashing when the elevator is leveling, to remind the passenger that it will landing.
Arrival chime	It can ring when the elevator is landing.
Remote monitoring	It can monitoring the running situation of elevator.
Earthquake shutdown function	When the earthquake device is moving, the elevator will landing at the nearest floor, and open the door.
Fireman operation	Firemen can use this elevator to travel to destination without responding to calling outside.
Self re-leveling	When the leveling is not accurate, it will re-leveling automatically.
Sub control panel	It just like the main accurate, it will re-leveling automatically.
Rear car operational panel	It control the rear opening and close.
The handicapped car operational panel	It specially designed for the handicapped people.
Group control	Through the group control to coordinate the running of many elevators.
The service for the rush hour of go to work	Only for group control, when the elevator runs up form the home floor with three more instructions, and other elevator in response to instructions and calls with automatically return to home floor and open doors.
The service for the rush hour of off work	Only for group control, when the elevator runs comes down from the home floor with three more instructions, and other elevator in response to instructions and calls will automatically return to home floor and open doors.
Dispersed waiting	Only for group control, when the elevator stops running in a specific time, the elevator will return to the pre-setting floor to shorten the call time for various floors to improve efficiency.
Isolated control of front and rear door	There are two kinds: one is the rear car operational board, the other is the call box outside the rear door.
Anti nuisance operation	It can cancel the disturbance instruction.
VIP service	It can cancel all the instruction and call until the VIP arrives the certain stop without any other stop.
Door remaining open function	Keep press the door open to delay of door closing.
LCD indicator	It can clearly indicate the floors and other information.

## Machine Roomless Passenger Elevator Construction Layout Drawing




### Machine roomless passenger specifications

Persons	Load (kg)	Speed (m/s)	Net size of car (mm)	Net size of door D.WxD.H(mm)	Shaft size (mm)		
			C.WxC.DxD.H	2P Central opening	H.WxH.D	HR.H	PIT
6	450	1.0	1100x1100x2300	800x2100	2050x1850	4200	1500
8	630	1.0	1400x1100x2300	800x2100	2250x1900	4200	1500
		1.5/1.75				4400	1600
10	800	1.0	1400x1350x2300	800x2100	2250x1950	4200	1500
		1.5/1.75				4400	1600
		2.0				4800	1800
		2.5				4800	2000
13	1000	1.0	1500x1550x2300	900x2100	2350x2150	4200	1500
		1.5/1.75				4400	1600
		2.0				4800	1800
		2.5				4800	2000
21	1600	1.0	1900x1800x2300	1100x2100	2850x2400	4500	1500
		1.5/1.75				4700	1600
		2.0				4900	1800
		2.5				5100	2000
26	2000	1.0	1900x2200x2300	1100x2100	2900x2600	4500	1500
		1.5/1.75				4700	1600
		2.0				4900	1800

Note: Only for reference, final manufacture please follow contract.



## Small Machine Room Elevator Construction Layout Drawing




Small machine room passenger specifications

Persons	Load (kg)	Speed (m/s)	Net size of car (mm)	Net size of door D.WxD.H(mm)	Shaft size (mm)			Shaft size (mm)						
			C.WxC.DxD.H	2P Central opening	H.WxH.D	HR.H	PIT	MR.WxMR.D	MR.H					
6	450	1.0	1400x850x2300	800x2100	2000x1800	4000	1500	2000x1800	2500					
		1.5/1.75				4400	1500							
8	630	1.0	1400x1100x2300	800x2100	2000x2050	4200	1500	2000x2050	2500					
		1.5/1.75				4400	1600							
10	800	1.0	1400x1350x2300	800x2100	2000x2300	4200	1500	2000x2300	2500					
		1.5/1.75				4400	1600							
		2.0				4800	1800							
		2.5				4800	2000							
		3.0				4200	1500							
13	1000 (1050)	1.0	1600x1450x2300 1100x2300x2300 (Residence/stretcher elevator)	900x2100	2200x2400 2050x2850 (Residence/ stretcher elevator)	4400	1600	2200x2400 2050x2850 (Residence/ stretcher elevator)	2500					
		1.5/1.75				4800	1800							
		2.0				4800	2000							
		2.5				5200	2600							
		3.0				5500	3100							
		3.5				6000	3850							
		4.0				4200	1500							
16	1250	1.0	1900x1450x2300	1100x2100	2500x2400	4200	1500	2500x2400	2500					
		1.5/1.75				4400	1600							
		2.0				4800	1800							
		2.5				4800	2000							
		3.0				5200	2600							
		3.5				5500	3100							
18	1350	1.0	1900x1550x2300	1100x2100	2500x2500	4200	1500	2500x2500	2500					
		1.5/1.75				4500	1600							
		2.0				4800	1800							
		2.5				4800	2000							
		3.0				5200	2600							
		3.5				5500	3100							
21	1600	1.0	1900x1800x2300	1100x2100	2500x2800	4200	1500	2500x2800	2500					
		1.5/1.75				4500	1600							
		2.0				4800	1800							
		2.5				4800	2000							
		3.0				5200	2600							
		3.5				6000	4000							
		4.0				6350	5000			4200x2900	2500			
		6.0				1900x1800x2300	1100x2100			2700x2900	6350	5000	4200x2900	2500
		10.0				1900x1800x2300	1100x2100			2800x3000	8800	7200	4300x3000	3800
		26				2000	1.0			1900x2200x2300	1100x2100	2700x2800	4500	1500
1.5/1.75	4700		1600											
2.0	5000		1800											
4.0	6000		3850											
6.0	6400		4000											
8.0	7500		6000											
10.0	1900x2200x2800		1100x2100	3200x3000	8800		7200	4700x3300	3800					

Note: Only for reference, final manufacture please follow contract.

## Semicircle Observation Elevator Construction Layout Drawing




Semicircle machine room / Machine roomless elevator specifications

Persons	Load (kg)	Speed (m/s)	Net size of car (mm) C.WxC.DxD.H	Net size of door D.WxD.H(mm) 2P Central opening	Shaft size (mm)			Machine room size (mm)	
					H.WxH.D	HR.H	PIT	MR.WxMR.D	MR.H
8	630	1.0	1100x1600x2300	700x2100	2200x2185	4500	1500	2200x2185	2500
		1.5/1.75				4700	1600		
10	800	1.0	1200x1800x2300	800x2100	2300x2355	4500	1500	2300x2355	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
13	1000	1.0	1300x1950x2300	900x2100	2400x2535	4500	1500	2400x2535	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
16	1250	1.0	1400x2150x2300	900x2100	2500x2600	4500	1500	2500x2600	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
18	1350	1.0	1500x2150x2300	1000x2100	2600x2600	4500	1500	2600x2600	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
21	1600	1.0	1500x2450x2300	1000x2100	2600x2900	4500	1500	2600x2900	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	1800		
		3.0				5200	1800		
		4.0				6000	1800		
26	2000	1.0	1700x2600x2300	1100x2100	2800x3050	4500	1500	2800x3050	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		3.0				5200	2600		
		4.0				6000	3850		

Note: Only for reference, final manufacture please follow contract.

## Square Observation Elevator Construction Layout Drawing




Square machine room / Machine roomless elevator specifications

Persons	Load (kg)	Speed (m/s)	Net size of car (mm) C.WxC.DxD.H	Net size of door D.WxD.H(mm) 2P Central opening	Shaft size (mm)			Machine room size (mm)	
					H.WxH.D	HR.H	PIT	MR.WxMR.D	MR.H
6	450	1.0	1100x1100x2300	800x2100	2050x1850	4200	1500		
8	630	1.0	1400x1100x2300	800x2100	2250x1900	4200	1500	/	/
		1.5/1.75				4400	1600		
10	800	1.0	1400x1350x2300	800x2100	2250x1950	4200	1500	/	/
		1.5/1.75				4400	1600		
		2.0				4800	1800		
		2.5				4800	2000		
13	1000	1.0	1500x1550x2300	900x2100	2350x2150	4200	1500	/	/
		1.5/1.75				4400	1600		
		2.0				4800	1800		
		2.5				4800	2000		
21	1600	1.0	1900x1800x2300	1100x2100	2850x2400	4500	1500	/	/
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
		3.0				5200	2600	2600x2900	2500
		4.0				6000	4900	3150x2400	2800
26	2000	1.0	1900x2200x2300	1100x2100	2900x2600	4500	1500	/	/
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		3.0				5200	2600	2800x3050	2500
		4.0				6000	4900	3150x2700	2800

Note: Only for reference, final manufacture please follow contract.



## Villa Elevator Construction Layout Drawing




### Villa elevator specifications

Persons	Load (kg)	Speed (m/s)	Net size of car (mm) C.WxC.DxD.H	Net size of door D.WxD.H(mm) 2P Central opening	Shaft size (mm)		
					H.WxH.D	HR.H	PIT
3	260	0.4	800x1150x2200	700x2000	1400x1500	3500	800
4	320	0.4	950x1300x2200	700x2000	1600x1600	3500	800
5	400	0.4	1200x1300x2200	800x2000	1850x1600	3500	800

Note: Only for reference, final manufacture please follow contract.

## Steel Structure Elevator Construction Layout Drawing




### Steel structure elevator specifications

Persons	Load (kg)	Speed (m/s)	Net size of car (mm) CWxCDxCH	Net size of door (mm)		Shaft size (mm)				
				OP	OPH	HW	HW (Single open)	HD (Through open)	K	S
6	450	1.0	1000x1300x2400	650x2100	1650	1700	1800	4500	1400	
		1.5						4600	1500	
8	630	1.0	1100x1400x2400	700x2100	1750	1800	1900	4500	1400	
		1.5						4600	1500	
10	800	1.0	1350x1400x2400	800x2100	2000	1800	1900	4500	1400	
		1.5						4600	1500	
13	1000	1.0	1500x1550x2400	900x2100	2150	1950	2050	4500	1400	
		1.5						4600	1500	

Note: Only for reference, final manufacture please follow contract.

## Bed Elevator Construction Layout Drawing




Machine room / Machine roomless bed elevator specifications

Persons	Load (kg)	Speed (m/s)	Net size of car (mm)	Net size of door (mm)	Shaft size (mm)			Machine room size (mm)	
					C.WxC.DxD.H	D.WxD.H	H.WxH.D	HR.H	PIT
21	1600	1.0	1400x2400x2300	1100x2100	2550x2900	4500	1500	2550x2900	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
		2.5				5100	2000		
24	1800	1.0	1600x2400x2300	1200x2100	2750x2900	4500	1500	2750x2900	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		
26	2000	1.0	1700x2400x2300	1200x2100	2850x2900	4500	1500	2850x2900	2500
		1.5/1.75				4700	1600		
		2.0				4900	1800		

Note: Only for reference, final manufacture please follow contract.

## Freight Elevator Construction Layout Drawing




Freight elevator specifications

Load (kg)	Speed (m/s)	Exterior size of car (mm)	Net door opening D.WxD.H(mm)	Shaft size (mm)			Machine room size (mm)		Door open type
				C.WxC.DxD.H	2P Central opening	H.WxH.D	HR.H	PIT	
630	0.5	1200x1500x2200	1100x2100	2100x1860	4200	1500	2500x3000	2200	Two panelside opening
1000	0.5	1500x1800x2200	1200x2100	2250x2160	4200	1500	3000x3000	2200	Two panelside opening
2000	0.5	1570x2900x2200	1500x2100	2700x3260	4200	1500	3500x3000	2500	Two panelside opening
	1.0				4500	1500			
	1.5	2850x2660		4500	1600	Four panelside opening			
	2.0			4800	1800				
3000	0.25	2070x3050x2200	1800x2100	3300x3410	4500	1500	3800x4200	2500	Four panel center opening
	0.5	2070x3100x2200	1800x2100	3300x3460	4500	1500	3800x4200	2500	Four panel center opening
3200	1.0	2070x3100x2200	1800x2100	3300x3460	4500	1500	3800x4200	2500	Four panel center opening
5000	0.25	2800x3400x2500	2000x2200	4200x3800	5000	1600	4200x3800	2800	Four panel center opening
	0.5	2800x3400x2500	2000x2200	4200x3800	5000	1600	4200x3800	2800	Four panel center opening
7000	0.25	3000x4200x2500	2600x2400	4500x4600	5000	1600	4500x4600	2800	Four panel center opening
	0.5	3000x4200x2500	2600x2400	4500x4600	5000	1600	4500x4600	2800	Four panel center opening
10000	2.0	3070x5760x2500	2600x2400	4900x6200	5000	1600	4900x6200	2800	Four panel center opening

Note: Only for reference, final manufacture please follow contract.



## Machine Roomless (MRL) Freight Elevator Construction Layout Drawing




Machine roomless(MRL) freight elevator specifications

Load (kg)	Speed (m/s)	Exterior size of car (mm)	Net door opening (mm)	Shaft size (mm)			Door open type
		C.WxC.DxD.H	D.WxD.H	H.WxH.D	HR.H	PIT	
1000	0.5	1500x1800x2200	1200x2100	2250x2200	4500	1500	Two panel side opening
	1.0				4500	1500	
	1.5				4600	1600	
	2.0				4800	1800	
2000	0.5	2000x2300x2200	1500x2100	3150x2660	4800	1500	Two panel side opening
	1.0				5000	1500	
	1.5				5200	1600	
	2.0				5200	1800	
3000	0.5	2470x2560x2200	1800x2100	3700x3000	5000	1600	Four panel center opening
5000	0.5	2800x3400x2500	2400x2400	4250x3800	6100	1600	Four panel center opening

Note: Only for reference, final manufacture please follow contract.

## Car Elevator Construction Layout Drawing




Car elevator specifications


Load (kg)	Speed (m/s)	Net door opening (mm)	Exterior size width x depth(mm)	Shaft size (mm)			Machine room size (mm)	Door open type
		width x height		H.WxH.D	HR.H	PIT	WxDxH	
3000	0.25/0.5	2400x2200	2700x5800	4100x6160	4800	1600	4100x6160x2500	Four panel center opening
5000	0.25 0.5	2600x2200	3500x7200	4750x7560			4750x7560x2500	Four panel center opening

Note: Only for reference, final manufacture please follow contract.

### 30° Escalator Construction Layout Drawing




Motor capacity (KW)	Traveling height (Ladder width) 1000		Traveling height (Ladder width) 800		Traveling height (Ladder width) 600	
	5.5	7.5	5.5	7.5	5.5	7.5
1000	1000	1158	1238	1400	1460	2310
800	800	958	1038	1400	1460	2110
600	600	758	838	1200	1260	1910
Step width	A	B	C	D	E	F
Model	Traveling height (mm)	Step width (mm)	Step depth (mm)	Step width (mm)	Step depth (mm)	Transporter dimension
<b>FHE(600)-30</b> (3600人/h) Speed: 0.5m/s	3000	57	46	41	2750	10900
	3500	60	49	44	2780	11890
	4000	64	52	47	2810	12880
	4500	68	56	50	2830	13870
	5000	71	59	53	2840	14860
<b>FHE(800)-30</b> (4800人/h) Speed: 0.5m/s	3000	59	52	47	2750	10900
	3500	63	56	50	2780	11890
	4000	67	60	54	2810	12880
	4500	71	64	57	2830	13870
	5000	74	68	60	2840	14860
<b>FHE(1000)-30</b> (6000人/h) Speed: 0.5m/s	3000	63	59	53	2750	10900
	3500	67	64	57	2780	11890
	4000	71	68	61	2810	12880
	4500	75	72	65	2830	13870
	5000	83	79	71	2840	14860




#### Instruction

1. When the escalator to be installed above the second floor. Don't have a pit. Layout drawing must be matched between up and down.
2. Keep the sufficient space at both EXIT and ENTRANCE of escalator. The width must be less than 1238. The depth from handrail belt reversed end to the front obstacle must be not less than 2500.
3. Space between handrail belt of escalator and obstacle must be not less than 500.
4. Motor AC 380 V 50 HZ. See in the table.
5. By the user to provide a grounding resistance of less than 4 ohms.
6. Provide by user to the main switch of the power requirements of 3 phases 5 wires.
7. All the dimensions are measured by MM.

### 35° Escalator Construction Layout Drawing



Motor capacity (KW)	Traveling height (Ladder width) 1000		Traveling height (Ladder width) 800		Traveling height (Ladder width) 600	
	5.5	7.5	5.5	7.5	5.5	7.5
1000	1000	1158	1238	1400	1460	2310
800	800	958	1038	1400	1460	2110
600	600	758	838	1200	1260	1910
Step width	A	B	C	D	E	F
Model	Traveling height (mm)	Step width (mm)	Step depth (mm)	Step width (mm)	Step depth (mm)	Transporter dimension
<b>FHE35/600</b> (3600人/h) Speed: 0.5m/s	3000	54	43	39	2860	10180
	3500	57	46	41	2890	11030
	4000	60	49	44	2920	11880
	4500	64	52	46	2940	12750
	5000	67	54	49	2970	13610
<b>FHE35/800</b> (4800人/h) Speed: 0.5m/s	3000	56	45	41	2860	10180
	3500	60	52	47	2890	11030
	4000	63	56	50	2920	11880
	4500	66	59	53	2940	12750
	5000	70	62	56	2970	13610
<b>FHE35/1000</b> (6000人/h) Speed: 0.5m/s	3000	60	56	50	2860	10180
	3500	64	60	53	2890	11030
	4000	67	64	57	2920	11880
	4500	71	67	60	2940	12750
	5000	74	71	64	2970	13610




#### Instruction

1. When the escalator to be installed above the second floor. Don't have a pit. Layout drawing must be matched between up and down.
2. Keep the sufficient space at both EXIT and ENTRANCE of escalator. The width must be less than 1238. The depth from handrail belt reversed end to the front obstacle must be not less than 2500.
3. Space between handrail belt of escalator and obstacle must be not less than 500.
4. Motor AC 380 V 50 HZ. See in the table.
5. By the user to provide a grounding resistance of less than 4 ohms.
6. Provide by user to the main switch of the power requirements of 3 phases 5 wires.
7. All the dimensions are measured by MM.





## 0° Moving Walk Construction Layout Drawing



Pedal width		1000		800	
Support opposite force (KN)	Quantity of center support beam L4	6000	10000	6000	10000
	R1	40	38	35	34
	R2	34.5	34	32	31
	R3	62.5	78.5	52	64.5
	R4	63.5	79.4	54	66.6
Motor capacity / rated current	R5	48	79.4	40	66.6
	conveyor length				
	10000-70000	8KW18A	10000-80000	8KW18A	
	70001-110000	11KW25A	80001-110000	11KW25A	

Technical notes	
Dip angle α	0-6°
Speed V	0.5m/s
Pedal type	aluminium alloy (indoor/half outdoor /complete outdoor)
Pedal width A	1000 800
Handrail center distance B	1238 1038
Moving walk outside width C	1600 1400
Machine supporting beam length D	≥1660 ≥1460
Installation place/drive mode	Length L1
Indoor/star delta	4000
Indoor/frequency	
Semi-outdoor/star delta	4600
Semi-outdoor/frequency	
Outdoor/star delta	4000
Outdoor/frequency	
Power supply	User needs to supply 380V 50Hz three-phase five-wire power supply. Voltage should ≤10 when moving walk at the start and the voltage should be ≤5 in normal operation. Maximum starting current should less than 3.5 times of rated current.

### Notes

- When the operating environment temperature under 0° (outdoor or semi-outdoor) need increase heater.
- Sufficient unblocked space is needed at entrance and exit of moving walk and the width should be the center distance at east.the depth(from handrail turn end) should be 2.5m at least,this area width should more than two times of the handrail center distance,the depth can be reduced to 2m.
- If have the pit should have waterproofing work(self-care by user).
- the distance between moving walk and any barrier should ≥ 500, or the Triangle place of handrail and floor should install protecting board (self-care by user).
- user provide power supply and earth connection equipment with resistance less than 4 ohm,it should leave Two meters left margin line under the upper supporting beams,motor capacity according to left form.
- Luminance at least should be 50Lx at entrance and exit of indoor moving walk,luminance at least should be 15Lx at entrance and exit of outdoor and semi outdoor(self-care by user).
- If the middle supporting beam use steel frame structure, please ask Hengda Fuji Elevator Company for advice.
- two sides and bottom decoration of moving walk self-care by user.



## Installation Notice

• Besides complying with the drawing of the contract, attention should also be drawn to the following

• To ensure the safety of the escalator and moving walk, free space should be large enough in the landing area. (See the minimum size left)

• C= the distance of the handrails

• Note: The graphical 1,2,3,4 safety devices function after the escalator installation and before the examination. They are at the users' own expense.



### Description

- Anti-creep device(5.5.2.2)
- Blocking device(5.5.2.2)
- Anti-skid device(5.5.2.2)
- Vertical apron(A.2.4)

Vertical apron	Clauses
b13,b14,b15,b16	5.2.2.2
b17≥100mm	5.5.2.2
h5≥0.30m	A.2.4
h9=(100±50)mm	5.5.2.2

Vertical apron	Clauses
h10=25mm-150mm	5.2.2.2
h11≥20mm	5.5.2.2
L5≥1000mm	5.5.2.2
b10=80mm	

• Note: Graphical representation is not proportional. It is only used for graphic illustration.

- Outer cover plate of escalator 1 moving walk shall install anti-creep device(1). Please refer to above table for installing height of anti-creep device and extension length L5 of outer cover plate. Its height shall be the same as that of handrail surface. It shall also accord with the graphic stipulations.
- When escalator / moving walk is adjacent to the wall, outer cover plate width b13> 125mm, blocking device (2) shall be installed in upper / lower end. It prevents the people from entering into outer cover plate area. When escalator 1 moving walk is adjacent to paralleled layout, common outer cover plate width b14> 125mm, the blocking device shall also be installed. It shall be extended to height h10.
- When handrail cover-plate which is close to handrail height is installed between escalator 1 inclined moving walk and adjacent wall, and distance between building (wall) and handrail central ling b15 is larger than 300mm, anti-skid device (3) shall be installed in handrail cover plate. Distance between anti-skid device and handrail shall ≥ b17. Spacing distance between anti-skid devices shall ≤ 1800mm. Height h11 shall ≥ 20mm. The device has no sharp angle /edge. As for adjacent escalator 1 inclined moving walk, when distance between handrail center-lines b15 > 400mm, anti-skid device shall be installed. It Shall also satisfy above requirements.



## Parts of Galaxy Fuji Vertical Platform Lift



### BRIEF INTRODUCTION

- Galaxy Fuji Vertical Lift Platform is suitable for wheelchair users, the elderly, children and people with reduced mobility.
- It is controlled by platform control panel and wireless remote control
- Driven by hydraulic power, it is highly efficient, stable and safe.
- Multiple safety device. With anti-drop function, when the drive chain breaks, the platform stops within 0.15 seconds; the bottom is equipped with a safety panel. If there are people or objects at the bottom, the platform cannot lower.
- All aluminum plate is optional.
- More than 85% of the external parts are made of rust-proof materials (stainless steel and aluminum alloy).
- 90° or 180° in and out
- The power supply uses single-phase power, and the control voltage uses DC24V safety voltage.
- PLC control system, safe and reliable.
- Platform load capacity 250Kg
- Lifting height is 800mm-10000mm
- Lifting speed is 60mm/s

## Two Access Options of Vertical Platform Lift




Straight Through Access




Adjacent Access


## Dimension of Straight Through Access Lift Platform



## Dimension of Adjacent Access Lift Platform



### Different Working Applications



(Unenclosed Lift)

(Shaftway Lift)

(Enclosure Lift)

### Normal Case



### Vertical Platform Lift With Glass Enclosure



Enclosure is Consist of Aluminum Frame and Tempered Glass





## Inclined Elevator

### The Main Sample



Qingdao Phoenix Boat

Outdoor type inclined elevator

### Condition

Indoor type: used in various buildings with incline operation requirements, such as subway stations, government agencies, high-end hotels, etc.

Outdoor type: used in the following places such as hillside scenic spots, tourist attractions, high-end hillside residences, karst caves or ski parks.

### The characteristics


The elevator normal operating environment temperature is  $-30^{\circ}\sim+45^{\circ}$  ;

The elevator can run normally under light rain condition and cannot be damaged under heavy rain condition;

The elevator can run normally under light snow condition and cannot be damaged under heavy snow condition;

The elevator can run normally under 6 wind condition and cannot be damaged under 8 wind condition;

In the frosting condition, the elevator can run normally after defrosting in slow motion.



### Technical parameter

Angle (°)	Load (kg)	Speed (m/s)	Car size (mm)			Door opening size (mm)		Well size (mm)		Travel (m)	Door opening pattern
			CW	CD	CH	OPW	OPH	HD	HW		
15~75	800	1.0 1.6	1350	1400	2300	900	2100	2000	2100	≤200	Front door/ side door
	1000	1.0 1.6	1400	1600	2300	900	2100	2200	2100	≤200	
	1350	1.0 1.6	1600	1900	2300	1000	2100	2500	2300	≤200	
	1600	1.0 1.6	1800	1900	2300	1000	2100	2500	2300	≤200	
	2000	1.0 1.6	2000	2100	2300	1200	2100	2800	2300	≤200	

# Hydraulic Guide Rail Cargo Elevator

## INTRODUCTION

Hydraulic guide rail cargo lift platform/cargo elevators are mainly installed in warehouse, workshop, logistics company, or rough building for lifting goods, the platform width size and horizontal size can refer to the user's real civil condition or construction condition.

The components of hydraulic cargo lifts are simple and stronger than ordinary elevators.

All of the ordinary elevator function and safety devices can be designed for hydraulic guide rail cargo elevators.

## Extraordinary advantages: Larger capacity! Larger car size! More flexible designing and installation!

Larger capacity-- maximum capacity can up to 20T!

Hydraulic lifts can be installed no matter if there are shaft or not!

Maximum car size can up to width 5.0m x depth 10.0m!



## Projects Installation Reference

### Style 1. Steel Structure Site

This installation is the easiest project, with the assistance of steel structure and connection beams, the installation will become simple, installation time will shorter, installation engineer's work will become simplified.



### Style 2. One Side Wall Site

Above photos show that only one side wall can support the whole lift's structure, the guide rail is the main steel structure of equipment, but the guide rails don't support any weight of the car, all of the car and goods' weight will give to lifting beam, chain and cylinder.



### Style 3. Shaft Wall Interior Site

These projects installation work same to traction machine elevator's installation work, but the installation work processing is simpler than normal elevators.





## Car Parking Lift



Single post car parking lift



Two post car parking lift



Four post car parking lift



Double wide 4 post car parking lift



Puzzle parking system



Stacker Parking Lift



4 post Triple stacker car parking lift



Scissor parking lift



Tilting car parking lift



Motor driven pit car parking system (PDK)



Hydraulic inclined pit parking lift



Hydraulic underground car parking lift (4 parking space)



Hydraulic underground parking system (UPS)



Hydraulic scissor underground parking system (USS)



hydraulic 2 post underground parking system(UTS)



Double-level Platform Scissor Lift



Scissor Lifting Platform

## Photovoltaic Power Generation System



### Features

- High-precision MPPT control to optimize the efficiency and increase photovoltaic power generation
- Flexible configuration, PV and grid charging optional, lithium battery&lead carbon battery accessible
- Wi-Fi, GPRS wireless monitoring modes
- Seamless switching between grid/off-grid modes
- EMS operating automatically

### Working modes

- When the battery energy exhausted,grid supplies the load at night.
- In the morning,solar power is not enough, grid and solar power supply local load together.
- Solar power is higher than load requirement , it charges the battery.
- It is cloudy in short time, the PV energy drop sharply, the battery discharges to the load.
- Once cloud disappears, the solar power continues to charge the battery.
- When the battery is full charged, solar power will feed back the grid.
- In the evening, the battery discharge to the load.

## Residential Pv&energy Storage Solution



### Features

- High- precision MPPT control to optimize the efficiency and increase photovoltaic power generation
- Flexible configuration, PV and grid charging optional, lithium battery&lead carbon battery accessible
- Wi-Fi, GPRS wireless monitoring modes
- Seamless switching between grid/off-grid modes
- EMS operating automatically

### Working modes

- When the battery energy exhausted,grid supplies the load at night.
- In the morning,solar power is not enough, grid and solar power supply local load together.
- Solar power is higher than load requirement , it charges the battery.
- It is cloudy in short time, the PV energy drop sharply, the battery discharges to the load.
- Once cloud disappears, the solar power continues to charge the battery.
- When the battery is full charged, solar power will feed back the grid.
- In the evening, the battery discharge to the load.



## Elevator & Escalator Modernization

### Updating and transformation solution

After assessed the elevator, we can develop the most appropriate generic solution based on the actual needs and budget.

From individual component retrofits to system upgrades and even entire elevator replacements, in addition to ensuring that elevators meet the latest safety and convenience standards, retrofits can also improve elevator performance and extend equipment life.

#### Elevator Replacement

We can replace the whole elevator in the original well. After our efficient work, you can have a brand-new modern elevator in the shortest time with lowest influence on residences.

#### Module Updating And Transformation

The updated and transformed tractor, control cabinet, and electric system are more reliable, more energy-saving, safer, and more convenient. Module transformation plans of General Elevator can selectively retain valuable parts to reduce cost and construction time for lowest influence on residential life.

### Component Upgrades

We can also provide upgrades for individual components. Updating the elevator components, such as the control system and the door system to upgrade the components of the elevator, can bring the following benefits:

#### Efficient And Energy Saving

Updated electric system, control system, and lift lighting system can significantly reduce energy consumption. These updates also reduce operation cost for higher efficiency and better energy saving.

#### Better Performance

Updated elevator parts including control system and lift system can lead to better elevator reliability, floor accuracy, waiting time, and continence.

#### Higher Safety

It is a prior task for every elevator to guarantee passenger and maintenance personnel's safety. Updated elevator parts including well, lift lighting, lift speed governor, and tractor shield greatly increase safety and manage risk.

### Escalator Updating And Transformation Solution

Compared to elevators, escalators are used in public sites including big markets, supermarkets, airports, and subways with numerous passengers. Physical deterioration and energy consumption are higher due to high use frequency. The escalators used for a long time need be updated and transformed to meet latest safety standards and reduce energy consumption as far as possible.

We provides plans including parts replacement and escalator replacement according to actual situation and user demand.

#### Escalator Replacement

Escalator replacement only needs several working days, leading to lowest influence on passengers. General Elevator's replacement plan can update escalator of high energy consumption and safety loophole into energy-saving and safe escalator. The saved cost can offset the updating and transformation cost. This flexible design not only increases safety and reliability, but also makes building more beautiful and harmonious.

#### Module Updating And Transformation

Module transformation plan guarantees the escalator to meet latest standards by means of most advanced technology upon lowest construction influence. General Elevator's module transformation plan can replace single parts or whole system upon demand. You can retain complete mechanical parts when improve device safety and appearance.

### Component Upgrades

We can also provide upgrades for individual components. Updating the elevator components, such as the control system and the door system to upgrade the components of the elevator, can bring the following benefits:

#### Control Module

Through scientific configuration, the original equipment is replaced by a new generation of intelligent vector elevator integrated control system, and the closed-loop vector control method makes the overall performance more stable, which can significantly improve safety and energy efficiency.

#### Appearance Module

GALAXYFUJI Elevator's module updating plan can replace parts including guard bar, stair plate, comb plate, skirt-board, plate, cleaning and balance stair lighting system to deliver an escalator appearance more suitable for the building.

#### Security Module

We can update your equipment by different solutions including stair deflection-resistance monitoring system, auxiliary brake, and additional safety mark to meet national safety standards and prevent safety loophole of public sites.